




HOW **PURE**  
IS YOUR **WATER?**®



## TDS-3 HANDHELD TDS METER WITH CARRYING CASE

*Ideal for all water purification applications, wastewater regulation, aquaculture, hydroponics, and colloidal silver. Perfect for both consumer or commercial use. Carry one in your pocket or toolbox at all times!*

### FEATURES

Ideal for commercial use. Includes a carrying case with belt clip.

Highly efficient and accurate due to its advanced microprocessor technology.

Hold Function: saves measurements for convenient reading and recording.

Auto-off function: the meter shuts off automatically after 10 minutes of non-use to conserve batteries.


Measurement Range: 0-9990 ppm. From 0-999 ppm, the resolution is in increments of 1ppm. From 1000 to 9990 ppm, the resolution is in increments of 10ppm, indicated by a blinking 'x10' image.

Built-in digital thermometer

Display: large and easy-to-read LCD screen.

Factory Calibrated: our meters are calibrated with a 342 ppm NaCl solution. Meters can be recalibrated with a mini-screwdriver.

Also available in "x10" mode: reads in increments only of 10 ppm (0-9990 ppm).



### SPECIFICATIONS

**TDS Range:** 0 - 9990 ppm (mg/L)

**Temp. Range:** 0 - 80 degrees Celsius

**Resolution:** 0-999: 1 ppm; 1000-9990: 10 ppm (indicated by a 'x10' icon)

**Temperature Resolution:** 0.1 degree Celsius (Celsius only)

**Accuracy:** +/- 2%

**EC-to-TDS Conversion Factor:** NaCl (avg. 0.5)

**ATC:** Built-in sensor for Automatic Temperature Compensation of 1 to 50 degrees Celsius (33 to 122 degrees Fahrenheit)

**Power source:** 2 x 1.5V button cell batteries (included) (LR44 or equivalent)

**Battery life:** 1000 hours of usage

**Dimensions:** 15.5 x 3.1 x 2.3cm (6.1 x 1.25 x 1 inches)

**Weight with case:** 76.5g (2.7 oz)

**Weight without case:** 56.7g (2 oz)

**3 YEAR WARRANTY** 