

Commercial/Industrial Rotationally Molded Brine Tanks



Commercial and industrial water softeners require a large volume of brine during each regeneration.

From a capacity of 95 gallons to 500 gallons, our Rotationally Molded Brine Tanks are built to last.

Molded out of durable, chemically resistant high density polyethylene, their 1/4" seamless walls won't bulge.

Rotationally Molded Brine Tanks are strong enough to handle your toughest brine requirements. (All tanks and covers are black.)

Operating Temperature Range:
40°F - 125°F (4.4°C - 51.6°C)

Also Available:

24" Plastic Grids

30" Plastic Grids

TANK SIZE	ORDER NUMBER	DIAMETER	HEIGHT	SALT CAPACITY	VOLUME	WEIGHT
24 x 60	G22460CB1P00	24"	60"	1000 lbs.	115 gal.	32 lbs.
30 x 60	G23060CB1P00	30"	60"	1600 lbs.	180 gal.	56 lbs.
39 x 48	G23948CB1P00	39"	48"	2200 lbs.	250 gal.	67 lbs.
39 x 60	G23960CB1P00	39"	60"	2700 lbs.	300 gal.	80 lbs.
42 x 60	G24260CB1P00	42"	60"	3100 lbs.	350 gal.	84 lbs.
50 x 60	G25060CB1P00	50"	60"	4500 lbs.	500 gal.	107 lbs.



www.clackcorp.com

Clack Corporation

4462 DURAFORM LANE • WINDSOR, WISCONSIN 53598-9716 USA
PHONE (608) 846-3010 FAX (608) 846-2586 SALES/CUSTOMER SERVICE FAX (800) 755-3010

Form No. 1837 • 8/31/2022