

## AQT-MFV-34 & AQT-MFV-1

### MANUAL FILTER VALVES

#### AQT-MFV-34 & AQT-MFV-1 Manual Filter Valves

Aquatrol AQT-MFV-34 & AQT-MFV-1 Manual Filter Valves offer a simple to use manually controlled valve for easy operation. Used with activated carbon filtration and other water treatment applications. The Aquatrol AQT-MFV-34 & AQT-MFV-1 Manual Filter Valves are available in 2.5" base and provide an easy to use lever operation for moving from Service, to Rinse and to Back Wash positions.



#### AQT-MFV-34 Specifications:

Temp Range:	41 °F - 113 °F (5 °C - 45 °C)
Pressure Range:	14 psi - 87 psi (0.96 bar - 5.99 bar)
Control Type:	Manual
Electricity:	None Required
Mounting Base:	2.5" 8 NPSM
Inlet:	3/4"
Outlet:	3/4"
Drain Line:	3/4"
Riser Pipe:	1.05" OD
Water Capacity Service:	9 gpm @ 21.8 psi (34.07 lpm @ 1.50 bar)
Water Capacity Back Wash:	8 gpm @ 21.8 psi (30.28 lpm @ 1.50 bar)
Filters:	6" - 10"

#### Material of Construction:

Body:	Noryl
Handle:	Metal
Internal Disc:	Ceramic



#### AQT-MFV-1 Specifications:

Temp Range:	41 °F - 113 °F (5 °C - 45 °C)
Pressure Range:	14 psi - 87 psi (0.96 bar - 5.99 bar)
Control Type:	Manual
Electricity:	None Required
Mounting Base:	2.5" 8 NPSM
Inlet:	1"
Outlet:	1"
Drain Line:	1"
Riser Pipe:	1.05" OD
Water Capacity Service:	19 gpm @ 21.8 psi (71.92 lpm @ 1.50 bar)
Water Capacity Back Wash:	19 gpm @ 21.8 psi (71.92 lpm @ 1.50 bar)
Filters:	6" - 12"

#### Material of Construction:

Body:	Noryl
Handle:	Metal
Internal Disc:	Ceramic

LIT-AQT-MFV-34-MFV-1-DS 06/17/20

**AQUATROL™**  
CONTROL VALVES

AQUATROL | P.O. Box 2235 Chino Hills, CA 91709USA

Distributed by:

WWW.AQUATROLTECH.COM