

ICF/ISF Series

Inline Filters

- ✓ Superior spring design to minimize channeling
- ✓ 1/4", 3/8" Female NPT and quick connections
- ✓ Sediment and coconut shell carbon



HYDRONIX ICF/ISF FILTER

utilize NSF listed coconut shell GAC and are designed to remove unpleasant taste and odor and reduce sediment to produce cleaner, clearer, better tasting water. Hydronix ICF Series Granular Activated Carbon Filters are easily installed on the water line to an automatic ice maker, Reverse Osmosis System or water dispensing system.

* For the complete list of our NSF Certified products, please visit the Hydronix Water Technology page on the official NSF website: www.nsf.org/certified-products-systems



Tested and certified by NSF International to ANSI/NSF Standard 42 for material requirements only.

| 2" DIAMETER SPECIFICATIONS | | | | | | |
|----------------------------|-------------|--|---------------|------------------------|--------------|--------------|
| | Part Number | Description | Case Quantity | Box Dimension (Inches) | Weight (lbs) | Weight (kgs) |
| 6" | ICF-6 | NSF Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" FNPT | 50 | 12.5 x 11 x 11 | 18 | 8.16 |
| | ICF-6Q | Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" Hydrofit™ QC | 50 | 12.5 x 11 x 11 | 18 | 8.16 |
| | ICF-6Q38 | Inline Coconut Filter: 1,000 Gallon, 2" x 6", 3/8" Hydrofit™ QC | 50 | 12.5 x 11 x 11 | 18 | 8.16 |
| 10" | ICF-10 | NSF Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" FNPT | 25 | 10.5 x 10.5 x 11 | 17 | 7.71 |
| | ICF-10Q | Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" Hydrofit™ QC | 25 | 11.5 x 10.5 x 10.5 | 17 | 7.71 |
| | ICF-10Q38 | Inline Coconut Filter: 2,000 Gallon, 2" x 10", 3/8" Hydrofit™ QC | 25 | 10.5 x 11 x 11 | 17 | 7.71 |
| | ISF-10 | Inline Sediment Filter: 2" x 10", 1/4" FNPT | 25 | 10.5 x 10.5 x 11 | 12 | 5.44 |
| | ISF-10Q | Inline Sediment Filter: 2" x 10", 1/4" FNPT Hydrofit™ QC | 25 | 11.5 x 10.5 x 10.5 | 12 | 5.44 |

| 2.5" DIAMETER SPECIFICATIONS | | | | | | |
|------------------------------|-------------|--|---------------|------------------------|--------------|--------------|
| | Part Number | Description | Case Quantity | Box Dimension (Inches) | Weight (lbs) | Weight (kgs) |
| 12" | ICF-2512 | NSF Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" FNPT | 25 | 13.25 x 11.75 x 13.5 | 26 | 11.79 |
| | ICF-2512Q | Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" Hydrofit™ QC | 25 | 13 x 12.5 x 13.5 | 27 | 12.25 |
| | ISF-2512 | Inline Sediment Filter: 2.5" x 12", 1/4" FNPT | 25 | 13.25 x 11.75 x 13.5 | 19 | 8.62 |
| | ISF-2512Q | Inline Sediment Filter: 2.5" x 12", 1/4" Hydrofit™ QC | 25 | 13.25 x 12.25 x 13.5 | 20 | 9.07 |

Available Port Sizes: 1/4" Female NPT Basic; 1/4" Hydrofit™ Quick Connect; and 3/8" Hydrofit™ Quick Connect.

*WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



ICF/ISF SERIES

Inline Filters
Data Sheet



ICF-10



ISF-10

Chlorine Taste & Odor Reduction - ICF-10 | ICF-10Q | ICF-10Q38

Coconut Shell Carbon

| | |
|---------------------|---------------------------|
| Service Life | 1 yr or 2000 gal (7570 L) |
| Maximum Flow | .50 gpm (1.9 lpm) |
| Maximum Pressure | 125 psi (8.6 bar) |
| Maximum Temperature | 100 °F (38 °C) |
| Minimum Temperature | 35 °F (2 °C) |

Materials of Construction

| | |
|-------------|----------------------|
| Shell: | Polypropylene |
| Media: | Coconut Shell Carbon |
| Inner Pads: | Polypropylene |

Available Port Sizes

- 1/4" Female NPT Basic
- 3/8" Female NPT Basic
- 1/4" Quick Connect
- 3/8" Quick Connect

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Distributed by:



Dirt & Sand Reduction - ISF-10 | ISF-10Q

| | |
|-------------------|-------------------|
| Service Life: | Applications vary |
| Maximum Flow: | .50 gpm (1.9 lpm) |
| Maximum Pressure: | 125 psi (8.6 bar) |
| Maximum Temp: | 100 °F (38 °C) |
| Minimum Temp: | 35 °F (2 °C) |
| Micron Rating: | 5M |

Materials of Construction

| | |
|--------|---------------|
| Shell: | Polypropylene |
| Media: | Polypropylene |

Applications

- Ice makers
- Reverse osmosis systems
- Water Coolers
- Coffee makers
- Refrigerators

HYDRONIX™
WATER TECHNOLOGY
An American Company

JUST ADD WATER™

P.O. Box 2235 Chino Hills, CA 91709 | USA
sales@hydronixwater.com • www.HydronixWater.com

LIT-ICF&ISF-DS 11/02/21